

Studiofoam® Pro

Acoustic Absorption Panel



FEATURES:

- 'Class A' Fire-Rated
- Superior Performance In 1.5" Thickness
- Easily mounts with Auralex® EZ-Stick Pro™ Tabs, Foamtak™ or Tubetak™ Pro

Studiofoam® Pro is a melamine-free acoustical foam with a Class A fire rating, per ASTM E84. With a slim 1.5" thickness, **Studiofoam Pro** offers all the traditional benefits of **Auralex's** industry leading **Studiofoam®** including durability & affordability while also offering outstanding acoustical performance with an overall NRC of 0.9.

Two sizes, 1.5" x 2' x 2' and 1.5" x 2' x 4', are available in a charcoal finish with beveled edges similar to our elegant **SonoFlat™** or **Pro Panel™** offerings.

Absorption Test Data (Absorption Coefficients):

125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	NRC
0.23	0.49	1.11	1.00	0.97	1.01	0.90



While many **Auralex** products are fire retardant and/or self extinguishing to varying extents, we cannot guarantee that any product meets the specific building code regulations in your area as regulations widely vary from place to place.

Check with your local fire marshal or building inspector for approval prior to purchasing or installing any of our products. **Auralex** will not be held liable for property damage or injuries caused by the misuse of our products.

For more information visit Auralex.com/tools/testing-data/fire-testing-data/

All copyrightable materials are ©Copyright Auralex Acoustics, Inc. 1994-2020. Auralex, Total Sound Control, Studiofoam and Real-World Acoustics are registered trademarks of Auralex Acoustics, Inc. All rights reserved. Proudly designed and manufactured in the U.S.A.

Real-World Acoustics®

1-800-959-3343 / 317-842-2600
9955 Westpoint Drive, Suite 101, Indianapolis IN USA 46256

1144-314.Studiofoam Pro Spec Sheet (12/26/2019 - 4:58 PM)