EZ-Stick Pro[™]

Installation & User Guide

TO APPLY:

- Mark the panel mounting position on the wall with small pencil marks or masking tape.
- Clean the attachment points on the wall surface with isopropyl or denatured alcohol, wipe gently and let dry. Avoid household cleaners, as their surfactants will degrade the bonding power of the *EZ-Stick Pro Mounting Tabs*.
- Separate the *EZ-Stick Pro Mounting Tabs* from each other.
- 4 Remove one of the paper release liners from the mounting tab.
- 6 Apply the tabs on the rear of the panel near the outside edges, oriented vertically for maximum holding strength. Apply very firm, uniform pressure (heel of hand, not the palm) for 30 seconds for maximum adhesion.
- 6 Remove the second paper release liner from the back side of the tab, position the panel with the target location on the wall and again press very firmly, with uniform pressure, for 30 seconds at each attachment point to secure.

NOTE: *EZ-Stick Pro Mounting Tabs* will damage the wall surface when removed and may not adhere well to some vinyl wallpapers. Caution should be used when mounting ceiling objects. Surfaces that are incompatible with the adhesive, improper cleaning or long-term environmental stresses may cause the bond to fail, for which *Auralex* is not liable. If the tabs get colder than 50° F (10° C), allow the *EZ-Stick Pro Mounting Tabs* to acclimate to their mounting environment for 48 hours before installation. Adhesive could soften and lose adhesion above 105° F (40° C).



1-800-959-3343 | 317-842-2600 | Auralex.com 9955 Westpoint Drive, Suite 101, Indianapolis IN USA 46256

1365-1115.EZ-Stick Pro User Guide (01/13/2020 - 11:18 AM)

Bound Control® Since

www.auralex.com

al Sound Control® Since

www.auralex.com

EZ-Stick Pro[™]

Real-World Acoustics

Installation & User Guide

TO APPLY:

- Mark the panel mounting position on the wall with small pencil marks or masking tape.
- Clean the attachment points on the wall surface with isopropyl or denatured alcohol, wipe gently and let dry. Avoid household cleaners, as their surfactants will degrade the bonding power of the *EZ-Stick Pro Mounting Tabs*.
- 6 Separate the EZ-Stick Pro Mounting Tabs from each other.
- 4 Remove one of the paper release liners from the mounting tab.
- 6 Apply the tabs on the rear of the panel near the outside edges, oriented vertically for maximum holding strength. Apply very firm, uniform pressure (heel of hand, not the palm) for 30 seconds for maximum adhesion.
- 6 Remove the second paper release liner from the back side of the tab, position the panel with the target location on the wall and again press very firmly, with uniform pressure, for 30 seconds at each attachment point to secure.

NOTE: *EZ-Stick Pro Mounting Tabs* will damage the wall surface when removed and may not adhere well to some vinyl wallpapers. Caution should be used when mounting ceiling objects. Surfaces that are incompatible with the adhesive, improper cleaning or long-term environmental stresses may cause the bond to fail, for which *Auralex* is not liable. If the tabs get colder than 50° F (10° C), allow the *EZ-Stick Pro Mounting Tabs* to acclimate to their mounting environment for 48 hours before installation. Adhesive could soften and lose adhesion above 105° F (40° C).



1-800-959-3343 | 317-842-2600 | Auralex.com 9955 Westpoint Drive, Suite 101, Indianapolis IN USA 46256

Real-World Acoustics*